

# E-1000RET2P2-5



Equinox manufactures a line of tanks for use with 2 or 3 compartments. These tanks are rated by retention capacity and meet standards outlined some regulating bodies. Some regional regulations require certain minimum retention capacities, which vary with the number of bedrooms per home. Confirm with your local regulatory authority.

All 2 and 3 compartment septic tanks have the working chamber divided in two by an extra divider. The following tanks are all CSA Certified and come complete with a 4" (101) ABS solvent weld coupling, street elbow, and 8" (202) of 4" (101) ABS pipe. Holding tanks come with a 4" (101) ABS solvent weld coupling, complete with suction pump-out fittings.

## 2 and 3 Compartment Sectional Fiberglass PUMP-OUT Tanks

## E-1000RET2P2-5

| TANK SPECIFICATIONS        |        |                                       |
|----------------------------|--------|---------------------------------------|
| APPROXIMATE SHIPPING SIZE  |        | NOMINAL CAPACITY                      |
| 60 x 60 (1525 x 1525)      |        | 1193 (5416)                           |
| CAPACITIES WORKING CHAMBER |        |                                       |
| NO.                        | TYPE   | CAPACITY (GALLONS)                    |
| 9                          | OUTLET | 426 (+ 75 Gallon Pump/Siphon Chamber) |
| 11                         | INLET  | 566                                   |

| MANHOLE SLEEVES |                 |
|-----------------|-----------------|
| LENGTH          | SLEEVE REQUIRED |
| 12 (305)        | 1 x E-MES-12    |
| 18 (457)        | 1 x E-MES-18    |
| 24 (610)        | 1 x E-MES-24    |
| 30 (762)        | 1 x E-MES-30    |
| 60 (1524)       | 1 x E-MES-60    |
| 84 (2134)       | 1 x E-MES-84    |

